

Product 70000072 Matting agent for VIASOL EP- and PU-coating systems

1 General Data

Product description / fields of application

VIASOL matting agent is a aggregat with a special fine grading curve based on polypropylene and will broadcasted onto VIASOL epoxy and polyurethane resin systems for producing anti-slip coatings and lightly matt surfaces.

Application

VIASOL matting agent is applicated by using a compressed air device (Chiron- or funnel-spray gun) into the fresh VIASOL self leveling coatings (eg VIASOL EP-C500) defined blown-in or broadcasted by hand.

The appearance of the surface depends on the type of application. The consumption values refer to the corresponding installation instructions or system planners. Please note, that for the application on conductive coatings do not exceed more than 15 - 20 g/m². After complete curing, the surfaces of the self leveling coatings are slip-resistant and are slightly matt.

Technical support

For further information relating to VIASOL products, please contact VIACOR Polymer GmbH directly.

Phone: +49 (0)7472-949990

E-Mail: info@viacor.de

Warnings and precautions

Information relating to the safe handling of this product can be found in the Material Safety Data Sheet. Local regulations concerning the safe handling of cleaning materials must be observed. Suitable protective clothing must be worn.

(A) Technical Data

Solid product

1. Grading curve	< 350 - 375 µm
2. Density	0,93 g/cm ³
3. Packaging	1 kg oder 10 kg pails
4. Shelf life (20 °C)	24 month
5. Storage	Dry at 10 – 25°C

Disclaimer

All information in this technical data sheet is based on our current knowledge and experience. This does not release the applicator from performing their own tests as many application factors, beyond our control, affect the application of our product. No guarantee of characteristics or suitability for a special purpose can be derived from this information. All present data, descriptions, drawings, photos, ratios, weights etc. are subject to change without prior notice and do not represent contracted characteristics of the product.

Due to different materials, sub-bases and working conditions, no guarantee of an application result or any liability claims can be derived from these details or from an unwritten technical advice except for liability claims based on:

-damage to life, body or health resulting from a negligent violation of obligations or a deliberate or negligent violation of obligation of a legal representative or assistant and

-if we are charged with intention or gross negligence.

The user has to test the products for their intended use. The user is responsible for following existing laws and orders and for observing third party trade mark rights.

As all VIACOR data sheets are updated on a regular basis it is the users responsibility to obtain the most recent issue (see www.viacor.de or contact us directly).

Manufacturer:

VIACOR Polymer GmbH, Graf-Bentzel-Str. 78, D-72108 Rottenburg, Tel: +49/7472-94999-0, info@viacor.de, www.viacor.de