

**Product 07193000**
**Glass fibers for VIASOL*DESIGN* levelling layers**

## 1 General Data

### Fields of application

VIASOL X930 glass fibers are used as a type of filler for VIASOL*DESIGN* levelling layers which are used if small holes and defects are available and a levelling in a one layer application is planned. Furthermore a slightly reinforcement will be achieved on substrates with small static cracks.

### Product description

VIASOL X930 are chopped strands of glass fibers with silane (E-glass).

### Application

VIASOL X930 E-glass fibers are added after the resin (comp. A + B) is mixed to a homogenous mixture and all other QS fillers are added and mixed. Then the glass fibers are added and mixed until homogenous.

Depending on the temperature and the used levelling layer type (N2 oder N3) and depending on the deepness of the holes / defects the right dosage must be determined with tests on the job site. As guideline we recommend to use at 20°C:

→ appr. 0,5 -1,0 % per weight.

(see also VIASOL*DESIGN* levelling layer application guidelines).

### Technical support

For further information relating to VIASOL products, please contact VIACOR Polymer GmbH directly.

Phone:+49 (0)7472-949990

E-Mail: info@viacor.de

### Warnings and precautions

Information relating to the safe handling of this product can be found in the Material Safety Data Sheet. Local regulations concerning the safe handling of cleaning materials must be observed. Suitable protective clothing must be worn.

### (A) Technical Data

#### Solid product

1. Solids content	100 %
2. Thickness of fibers	appr. 13,0 +/- 3 µm
3. Length of fibers	appr. ca. 6 mm
4. Packaging	20 kg sacs
5. Shelf life (20 °C)	12 month
6. Storage	Dry at 15 – 25°C, avoid direct sunlight

### Disclaimer

All information in this technical data sheet is based on our current knowledge and experience. This does not release the applicator from performing their own tests as many application factors, beyond our control, affect the application of our product. No guarantee of characteristics or suitability for a special purpose can be derived from this information. All present data, descriptions, drawings, photos, ratios, weights etc. are subject to change without prior notice and do not represent contracted characteristics of the product.

Due to different materials, sub-bases and working conditions, no guarantee of an application result or any liability claims can be derived from these details or from an unwritten technical advice except for liability claims based on:

-damage to life, body or health resulting from a negligent violation of obligations or a deliberate or negligent violation of obligation of a legal representative or assistant and

-if we are charged with intention or gross negligence.

The user has to test the products for their intended use. The user is responsible for following existing laws and orders and for observing third party trade mark rights.

As all VIACOR data sheets are updated on a regular basis it is the users responsibility to obtain the most recent issue (see [www.viacor.de](http://www.viacor.de) or contact us directly).

### Manufacturer:

VIACOR Polymer GmbH, Graf-Bentzel-Str.78, D-72108 Rottenburg, Tel: +49/7472-94999-0, [info@viacor.de](mailto:info@viacor.de), [www.viacor.de](http://www.viacor.de)